

To: Benjamin Avery Date: January 31, 2020 Riverside Partners, LLC

Project #: 58036.00

From: Jenn Conley, PE Re: Riverside Independent Living

Erica Quallen Traffic Impact Study
Burlington, VT

VHB has conducted a Traffic Impact Study (TIS) for the proposed Riverside Independent Living facility to be located at 362-374 Riverside Avenue, with access from Hillside Terrace in Burlington, Vermont.

The proposed facility will have approximately 60 units and is located on the southern side of Riverside Avenue between the loop ends of Hillside Terrace, with the access and egress point being adjacent to the westernmost intersection of Hillside Terrace and Riverside Avenue.

This Traffic Impact Study includes the following elements:

- A description of the existing roadway network in the vicinity of the site;
- A summary of the crash data within the study area;
- A description of the proposed development program;
- A trip generation estimate for the proposed development program;
- An evaluation of anticipated traffic changes for the adjacent roadway and intersections in the vicinity;
- An evaluation of traffic operations within the study area; and
- Conclusions and recommendations to support the project.

As part of this study, three different intersections were evaluated and summarized in regard to level of service (LOS) and average delay in order to estimate how the proposed project impacts the local street network. The traffic study intersections are shown in **Figure 1**.

EXISTING CONDITIONS

The project is located on Hillside Terrace, specifically on the northwest segment of the loop. Hillside Terrace is a loop road with both ends connecting to Riverside Avenue. The driveway for the proposed redevelopment is located approximately 125-feet from the west intersection of Riverside Avenue and Hillside Terrace. The location of the site in relation to the local roadway network is shown in **Figure 1**.



Figure 1: Sie Location Map



Roadway Characteristics

Hillside Terrace is a residential loop road providing access to the homes on Hillside Terrace as well as one adjacent housing development. Hillside Terrace connects on both sides to Riverside Avenue forming intersections approximately 300-feet apart along Riverside Avenue. The western intersection is an unsignalized intersection with Hillside Terrace operating under stop-control. The eastern intersection is signalized with Hillside Terrace being an actuated approach. Hillside Terrace provides sidewalks on the inner side of the loop which connect to sidewalks on Riverside Avenue.



Riverside Avenue serves as a segment of US Routes 2 and 7 and is an east-west principal arterial that parallels the Winooski River, connecting Burlington's Old North End neighborhood to downtown Winooski. In the vicinity of the project site, it is a 25 mile per hour roadway carrying between 15,000 and 16,000 vehicles per day¹.

SAFETY ASSESSMENT

A review of VTrans' most recent High Crash Location (HCL) Report (2012-2016) revealed no roadway segments or intersections within the project study area classified as an HCL by VTrans². In addition, the VTrans Public Crash Data Query Tool was reviewed to investigate project area crashes for the most recent 5-year period available: January 1, 2014 through December 31, 2018. **Table 1** below summarizes the reported crashes for the primary study area over the recent five-year period. Additional detail of the crashes is included in the Appendix.

Table 1: Summary of 2014-2018 Reported Crashes

Location	Number of Crashes	Injury Crashes	Fatal Crashes	Property Damage Only	Rear End Crashes	Turning Vehicle Crashes	Wet/Snowy Road Conditions
Riverside Avenue and Hillside Terrace	25	7 (28%)	0	18 (72%)	10 (40%)	5 (20%)	5 (20%)

TRAFFIC NETWORKS

Seasonal Variation

Since it is impractical to design for the highest volume encountered during the year, VTrans guidelines recommend a compromise between capacity and cost. Design Hourly Volume (DHV) criteria allow roads to be designed for the 30th highest hourly volume of the year. VTrans Riverside Avenue Average Annual Daily Traffic (AADT) traffic volume data was obtained. The appropriate VTrans DHV adjustment factors for volumes and roadway type were researched and applied to the AADT.³ Detailed calculations for the DHV adjustments are provided in the Appendix.

Background Growth

Background traffic growth is a function of expected land development in the region. To predict a rate at which traffic can be expected to grow during the forecast period, historical traffic growth was examined. The regression analysis chart in the 2017 VTrans Redbook⁴ suggests a background growth rate of 1.03 for projecting traffic volumes from 2020 to 2025. VTrans regression analysis is provided in the Appendix.

¹ Vermont Agency of Transportation Highway Division Traffic Research Unit, 2018 (Route Log) AADTs: State Highways. May 2019.

² <u>High Crash Location Report: Intersections and Segments (2012-2016)</u>, Vermont Agency of Transportation Office of Highway Safety Division.

³ ATR Station D156

⁴ Continuous Traffic Counter Report (The Redbook), Vermont Agency of Transportation, 2017.



Other Development

Based on review of proposed developments in the vicinity of the project site, one project undergoing the Burlington Design Review Board process was found that was included in the background traffic volumes for this project. A housing development at 110 Riverside Avenue is being proposed and is anticipated to generate 21 weekday AM peak hour trips and 26 weekday PM peak hour trips. The trip distribution shown in the Trudell Consulting Engineers November 2019 traffic analysis was used to add these trips to the network being analyzed in this traffic analysis. A copy of the relevant data from the Trudell study can be found in the Appendix.


No Build Traffic Networks


The 2020 and 2025 No Build traffic volumes were developed by applying the growth factors from the VTrans regression analysis chart to DHV-adjusted peak hour traffic volumes and adding the other identified project traffic. The 2020 and 2025 No Build weekday AM and PM volumes are shown in **Figure 2**.

 $\label{thm:linear_transform} \label{thm:linear_transform} \label{thm:lin$



Figure 2: 2020 and 2025 No Build Traffic Volumes





Legend AM Peak Hour (PM Peak Hour)




Figure 2 No Build Weekday Peak Hour Traffic Volumes



PROPOSED DEVELOPMENT

The proposed facility will have approximately 60 independent living residential units and is located on the southern side of Riverside Avenue between the loop ends of Hillside Terrace, with the access and egress point being adjacent to the western intersection of Hillside Terrace and Riverside Avenue. The proposed layout of the project site is shown below in **Figure 3**.

Figure 3: Proposed Site Plan



TRIP GENERATION

Trip estimates for the proposed development were calculated based on rates published by the Institute of Transportation Engineers (ITE) in the 10th edition of the Trip Generation Manual for the weekday AM and PM peak hours. These time periods are typically the highest volume times on the adjacent roadway network and are used for this analysis. ITE land use code (LUC) 252 – Senior Adult Housing, Attached was used to estimate peak hour




trips of the proposed development. Based on ITE estimates, the independent living facility would be expected to generate 12 trips during the weekday AM peak hour and 17 vehicle trips during the PM peak hour. **Table 2** summarizes the trip generation estimate for the proposed development. The distribution of these trips onto the roadway network was based on current travel patterns and is shown in **Figure 4**.

Table 2: Trip Generation Summary

Peak Period	Total Peak Hour Site Generated Trips
Weekday AM	
Enter	4
Exit	<u>8</u>
Total	12
Weekday PM	
Enter	9
Exit	<u>8</u>
Total	17

Figure 4: Site Generated Trip Distribution







Build Traffic Networks

The 2020 and 2025 Build traffic volumes were developed by combining the No Build volumes and site generated trips. The 2020 and 2025 Build weekday AM and PM volumes are shown in **Figure 2**.

Figure 5: 2020 and 2025 Build Traffic Volumes





Legend AM Peak Hour (PM Peak Hour)





TRAFFIC ANALYSES

Intersection capacity analyses were performed for the study area intersections. Levels of service (LOS) were calculated based on the criteria published in the *2000 Highway Capacity Manual*.⁵ Level of service is the term that defines the conditions that may occur on a given roadway or at an intersection when accommodating various traffic volume loads. Levels of service range from A to F with LOS A representing generally free flowing operating conditions and LOS F representing generally congested conditions. Copies of the LOS calculations are provided in the Appendix.

Table 3 summarizes the operational analysis at the *unsignalized* study area intersection during the 2020 and 2025 weekday AM and PM peak hours under No Build and Build conditions. As shown in the table, Hillside Terrace West at Riverside Avenue experiences only two to five second increases in delay from the No Build to Build scenarios in both peak hours. LOS E is typically regarded as a deficient level of service, but it should be noted that the volume to capacity ratio is only 0.14 in the Build scenario is just over the threshold of 35 seconds of delay to be defined as LOS E. The major approach will operate at LOS A as it continues to experience free-flow conditions. The unsignalized intersection of Hillside Terrace and the site driveway will operate at LOS A from all approaches, in all conditions.

Table 4 summarizes the operational analysis at the *signalized* study area intersections during the 2020 and 2025 weekday AM and PM peak hours under No Build and Build conditions. As shown in the table, the signalized intersection of Hillside Terrace East and Riverside Avenue is expected to operate overall at LOS C or better in 2020 and 2025 both without and with the project. Project related delays are expected to be less than one second per vehicle. Overall the results indicate that the infrastructure has been built to accommodate the growth anticipated in this area.

Table 3: Unsignalized Intersection Capacity Analysis

		2	020 No Bui	ld		2020 Build		2	025 No Buil	d		2025 Build	
	Intersection / Movement	v/c ⁺	Delay*	LOS **	v/c	Delay	LOS	v/c	Delay	LOS	v/c⁺	Delay*	LOS **
	Hillside Terrace West at Riverside Ave												
Ξ.	EB from Riverside Ave	0.34	0.0	Α	0.34	0.0	Α	0.35	0.0	Α	0.35	0	Α
Hour	WB from Riverside Ave	0.00	0.0	Α	0.00	0.1	Α	0.00	0.0	Α	0.00	0.1	Α
K	NB from Hillsde Terrace	0.03	28.5	D	0.07	30.0	D	0.03	30.5	D	0.08	32.2	D
Peak	Hillside Terrace West at Site Driveway												
Α M	WB from Site Driveway	DOES NO	T EXIST IN		0.01	8.4	Α	DOES NO	T EXIST IN I		0.01	8.4	Α
٩	NB from Hillside Terrace		CONDITION		0.00	0.0	Α		CONDITION		0.00	0.0	Α
	SB from Hillside Terrace		CONDITION	•	0.00	3.2	Α		CONDITION		0.00	3.2	Α
	Hillside Terrace West at Riverside Ave												
=	EB from Riverside Ave	0.54	0.0	Α	0.55	0.0	Α	0.56	0.0	Α	0.56	0.0	Α
Hour	WB from Riverside Ave	0.00	0.0	Α	0.01	0.1	Α	0.00	0.0	Α	0.01	0.2	Α
~	NB from Hillsde Terrace	0.07	32.0	D	0.14	36.7	Е	0.08	35.4	E	0.15	40.4	E
Peak	Hillside Terrace West at Site Driveway												
Σ	WB from Site Driveway	DOES NO	T EXIST IN		0.01	8.4	Α	DOES NO	T EVICT IN I		0.01	8.4	Α
_	NB from Hillside Terrace		CONDITION		0.01	0.0	Α	DOES NOT EXIST IN NO BUILD			0.01	0.0	Α
	SB from Hillside Terrace		COMDITION	1	0.01	4.7	Α	CONDITION		0.01	4.7	Α	

Volume to capacity ratio

^{*} Delay expressed in seconds per vehicle

^{**} Level of Service

⁵ Highway Capacity Manual, Federal Highway Administration, Transportation Research Board, 2000.



Table 4: Signalized Intersection Capacity Analysis

		2	020 No Bui	ld		2020 Build		2	025 No Buil	ld		2025 Build	
	Intersection / Movement	v/c ⁺	Delay*	LOS **	v/c	Delay	LOS	v/c	Delay	LOS	v/c⁺	Delay*	LOS **
ur	Hillside Terrace East at Riverside Ave												
훈	EB from Riverside Ave	0.50	10.3	В	0.50	10.3	В	0.51	10.5	В	0.51	10.5	В
	WB Left Turn from Riverside Ave	0.02	6.1	Α	0.02	6.1	Α	0.02	6.1	Α	0.02	6.1	Α
Peak	WB Through from Riverside Ave	0.57	10.1	В	0.57	10.1	В	0.59	10.3	В	0.59	10.4	В
ΑM	NB from Hillsde Terrace	0.11	30.7	C	0.11	30.7	C	0.11	30.8	C	0.11	30.8	C
٩	Overall	0.45	11.2	В	0.45	11.3	В	0.46	11.5	В	0.47	11.5	В
_	Hillside Terrace East at Riverside Ave												
Hour	EB from Riverside Ave	0.71	14.6	В	0.71	14.7	В	0.73	15.3	В	0.74	15.4	В
	WB Left Turn from Riverside Ave	0.17	7.1	Α	0.17	7.1	Α	0.19	7.2	Α	0.19	7.3	Α
Peak	WB Through from Riverside Ave	0.67	11.8	В	0.67	11.9	В	0.69	12.3	В	0.69	12.4	В
Σ	NB from Hillsde Terrace	0.08	30.3	C	0.08	30.3	C	0.08	30.3	C	0.08	30.3	C
_	Overall	0.55	13.6	В	0.55	13.7	В	0.57	14.1	В	0.57	14.2	В

^{*} Volume to capacity ratio

CONCLUSIONS

The proposed project consists of constructing a new 60-unit Independent Living at 362-374 Riverside Avenue, with access from Hillside Terrace in Burlington, Vermont. The trip generation estimates conducted for this study indicate that the proposed development program will generate approximately 12 new vehicle trips during the weekday AM peak hour and 17 new vehicle trips during the weekday PM peak hour.

Primary access and egress will be provided via the existing residential access off Hillside Terrace which has experienced no reported crash history and is not expected to decrease in safety with the addition of this driveway. A LOS E is expected from the Hillside Terrace West approach at Riverside Avenue, but the proposed development is not likely to increase delay by more than five seconds compared to the No Build scenario. The project related delay increases are less than two seconds per vehicle at each of the study area intersections.

In conclusion, based on the results of this Traffic Impact Study, the proposed Independent Living facility project is not anticipated to generate unreasonable congestion or unsafe conditions on the adjacent roadway network.

^{*} Delay expressed in seconds per vehicle

^{**} Level of Service



Appendices

- A. Traffic Volume Data
- B. Crash Data
- C. Trip Generation Summary
- D. 110 Riverside Avenue Traffic Impact Analysis
- E. Intersection Capacity Analysis



Appendix A

Traffic Volume Data

Intersection: Riverside Ave and Hillside Terr West

Town:

Start Date:

Burlington, VT 7/16/2019 Counter: VTrans Site Code:

0 0 0 0 175 0 0 1 0 0 4 1 149 0

VHB 0

Vihb

Project: Riverside IL Housing

Checked by:

Location: Burlington, VT

Calculated by: ELQ

Project #: 58036 Sheet:

Date: 12/11/19 Date:

TMC - Riverside Ave and Hillside Terr West
PEAK HOUR CALCULATIONS

TURNING MOVEMENT COUNT DATA - Totals by Movement

_	TURNING MC	VEMEN	IT COUN	IT DATA	- Totals	by Mov	ement											PEAK HOUR C	ALCULAT	IONS					
				SB			١	NΒ				NB				EB									
			1	N/A			Rivers	side Ave			Hillside	e Terrace			Rivers	ide Ave		1 HR TOTALS							
	Start Time	Right	Thru	Left	Peds	Right	Thru	Left	Peds	Right	Thru	Left	Peds	Right	Thru	Left	Peds	Begin Time	SB	WB	NB	EB	TOTAL	_	
1	06:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	06:00 AM	0	0	0	102	102	_/	
2	06:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	06:15 AM	0	97	0	217	314		
3	06:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	06:30 AM	0	245	0	366	611		
4	06:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	102	0	0	06:45 AM	0	400	1	519	920		
5	07:00 AM	0	0	0	0	0	97	0	0	0	0	0	1	0	115	0	0	07:00 AM	0	586	3	563	1152		
6	07:15 AM	0	0	0	0	0	148	0	0	0	0	0	1	1	148	0	0	07:15 AM	0	662	3	584	1249		
7	07:30 AM	0	0	0	0	1	154	0	0	0	0	1	1	2	151	0	0	07:30 AM	0	677	4	570	1251		
8	07:45 AM	0	0	0	0	0	186	0	0	0	0	2	0	1	145	0	0	07:45 AM	0	669	4	576	1249		
9	08:00 AM	0	0	0	0	0	173	0	0	0	0	0	1	1	135	0	0	08:00 AM	0	662	3	436	1101		
10	08:15 AM	0	0	0	0	0	163	0	0	0	0	1	1	1	134	0	0	08:15 AM	0	489	3	300	792		Cell ref.: 7
11	08:30 AM	0	0	0	0	0	147	0	0	0	0	1	2	1	158	0	0	08:30 AM	0	326	2	165	493	>	AM Peak Hr
12	08:45 AM	0	0	0	0	0	179	0	0	0	0	1	2	1	5	0	0	08:45 AM	0	179	1	6	186		07:30 AM - 8:30 AM
13	09:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	09:00 AM	0	0	0	0	0		Vol. = 1251
14	09:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	09:15 AM	0	0	0	0	0		10 1251
15	09:30 AM	0	0	0	0		0	0	0	0	0	0	0	1 0	0	0	0	09:30 AM	0	0	0	0	0		
16	09:45 AM	0	0	0	0		0	0	0	0	0	0	0	0	0	0	0	09:45 AM	0	0	0	0	0		
17	10:00 AM	0	0	0	0		0	0	0	0	0	0	0	1 0	0	0	0	10:00 AM	0	0	0	0	0		
	10:00 AM		0	0	0		0	0	0	0	0	0	0	0	0	0		10:00 AW 10:15 AM	0	0	0	0	0		
18	10:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0 0	10:30 AM	0	0	0	0	0		
19	10:35 AM			0	-		_		0	_	_	_	_	0	_	_		10:45 AM	-	0	0	0	-		
20		0	0 0	_	0	0	0	0	0	0	0	0	0		0	0 0	0		0 0	0	0	0	0		
21	11:00 AM	0	_	0	0		0	0	Ū		0	0	0		0	-	0	11:00 AM	-	ū	0	0	0		
22	11:15 AM	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	11:15 AM	0	0	0	0	0		
23	11:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	11:30 AM	0	0	0	0	0		
24	11:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	11:45 AM	0	0	0	0	0	- _	
25	12:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	12:00 PM	0	0	0	0	0		>
26	12:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	12:15 PM	0	0	0	0	0		
27	12:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	12:30 PM	0	0	0	0	0		
28	12:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	12:45 PM	0	0	0	0	0		
29	01:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	01:00 PM	0	0	0	0	0		
30	01:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	01:15 PM	0	0	0	0	0		
31	01:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	01:30 PM	0	0	0	0	0	/	
32	01:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	01:45 PM	0	0	0	0	0		
33	02:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	02:00 PM	0	0	0	0	0		
34	02:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	02:15 PM	0	0	0	0	0	(Cell ref.: 43
35	02:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	02:30 PM	0	0	0	0	0	\geq	PM Peak Hr
36	02:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	02:45 PM	0	0	0	0	0		04:30 PM - 5:30 PM
37	03:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	03:00 PM	0	0	0	0	0		Vol. = 1687
38	03:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	03:15 PM	0	166	0	169	335		
39	03:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	03:30 PM	0	327	4	343	674		
40	03:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	03:45 PM	0	512	10	551	1073		
41	04:00 PM	0	0	0	0	0	165	1	0	0	0	0	0	0	169	0	0	04:00 PM	0	704	11	788	1503		
42	04:15 PM	0	0	0	0	0	159	2	0	2	0	2	1	5	169	0	0	04:15 PM	0	731	14	830	1575		
43	04:30 PM	0	0	0	0	0	185	0	0	4	0	2	3	1	207	0	0	04:30 PM	0	776	10	901	1687		
44	04:45 PM	0	0	0	0	0	192	0	0	1	0	0	4	2	235	0	0	04:45 PM	0	776	6	854	1636		
45	05:00 PM	0	0	0	0	0	193	0	0	2	0	1	3	1	210	0	0	05:00 PM	0	759	6	767	1532	\mathcal{I}	
46	05:15 PM	0	0	0	0	0	206	0	0	0	0	0	1	1	244	0	0								
47	05:30 PM	0	0	0	0	0	183	2	0	2	0	0	0	1	160	0	0								
		I _	_	_	_	1 _		_	_	1 .	_	_	_	1 .		_	_								

Riverside Ave and Hillside Terr East Intersection:

Town:

Start Date:

Burlington, VT 7/16/2019

Counter: VTrans Site Code: VHB 0

Project: Riverside IL Housing

Location: Burlington, VT Calculated by: ELQ Checked by:

TMC - Riverside Ave and Hillside Terr East

58036 Project #: Sheet: Date: 12/11/19

Date:

TURNING MOVEMENT COUNT DATA - Totals by Movement

PEAK HOUR CALCULATIONS

ı	TURNING MC	VEME	NT COUN	IT DATA	- Totals I	by Mov												PEAK HOUR (CALCULAT	IONS					
				SB				WB				NB				EB									
				N/A				side Ave				e Terrace				side Ave		1 HR TOTALS							
	Start Time	Right	Thru	Left	Peds	Right	Thru	Left	Peds	Right	Thru	Left	Peds	Right	Thru	Left	Peds	Begin Time	SB	WB	NB	EB	TOTAL	_	
1	06:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	06:00 AM	0	0	0	107	107		
2	06:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	06:15 AM	0	95	10	218	323		
3	06:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	06:30 AM	0	236	24	370	630		
4	06:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	107	0	0	06:45 AM	0	382	45	524	951		
5	07:00 AM	0	0	0	0	0	95	0	0	6	0	4	1	0	111	0	0	07:00 AM	0	565	58	566	1189		
6	07:15 AM	0	0	0	0	0	141	0	0	6	0	8	0	0	152	0	0	07:15 AM	0	634	66	589	1289		
7	07:30 AM	0	0	0	0	0	146	0	0	14	0	7	1	1	153	0	0	07:30 AM	0	658	68	573	1299		
8	07:45 AM	0	0	0	0	0	181	2	2	9	0	4	0	3	146	0	2	07:45 AM	0	656	57	581	1294		
9	08:00 AM	0	0	0	0	0	162	2	2	9	0	9	1	4	130	0	0	08:00 AM	0	648	63	437	1148		
10	08:15 AM	0	0	0	0	0	162	3	3	10	0	6	1	3	133	0	0	08:15 AM	0	484	45	303	832		Cell ref.: 7
11	08:30 AM	0	0	0	0	0	142	2	2	5	0	5	3	5	157	0	0	08:30 AM	0	319	29	167	515	\rightarrow	AM Peak Hr
12	08:45 AM	0	0	0	0	0	172	3	3	12	0	7	0	1	4	0	0	08:45 AM	0	175	19	5	199		07:30 AM - 8:30 AM
13	09:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	09:00 AM	0	0	0	0	0		Vol. = 1299
14	09:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	09:15 AM	0	0	0	0	0		
15	09:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	09:30 AM	0	0	0	0	0		
16	09:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	09:45 AM	0	0	0	0	0		
17	10:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	10:00 AM	0	0	0	0	0		
18	10:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	10:15 AM	0	0	0	0	0		
19	10:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	10:30 AM	0	0	0	0	0)	
20	10:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	10:45 AM	0	0	0	0	0)	
21	11:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	11:00 AM	0	0	0	0	0		
22	11:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	11:15 AM	0	0	0	0	0		
23	11:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	11:30 AM	0	0	0	0	0		
24	11:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	11:45 AM	0	0	0	0	0	- [(
25	12:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	12:00 PM	0	0	0	0	0		
26	12:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	12:15 PM	0	0	0	0	0		
27	12:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	12:30 PM	0	0	0	0	0		
28	12:45 PM	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	12:45 PM	0	0	0	0	0		
29	01:00 PM	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	01:00 PM	0	0	0	0	0		
30	01:15 PM	0	0	0	0	0	0	0 0	0	0	0	0	0	0	0	0	0	01:15 PM	0	0	0	0	0		į
31	01:30 PM 01:45 PM	0	0	0	0	0	O	U	0	Ŭ	Ū	0	Ū	1 "	0	0	0	01:30 PM	0	0	Ū	0	Ū		
32	01:45 PM 02:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	01:45 PM	0	0	0	0	0		
33	02:00 PM 02:15 PM	0	0 0	0 0	0 0	0	0 0	0 0	0	0	0 0	0 0	0 0	0	0 0	0 0	0 0	02:00 PM 02:15 PM	0 0	0 0	0 0	0 0	0		Cell ref.: 43
34	02:30 PM		0	0	0		0	0	0	0	0	0	0		0	0	0	02:30 PM	0	0	0	0	0 0		PM Peak Hr
35	02:30 PM 02:45 PM	0	0	0	0		0	0	0	0	0	0	0	0	0	0	0	02:45 PM	0	0	0	0	0		04:30 PM - 5:30 PM
36	02:43 PM 03:00 PM	0	0	0	0		0	0	0	0	0	0	0	0	0	0	0	03:00 PM	0	0	0	0	0		Vol. = 1658
37	03:15 PM			0	0		0	_	0	0	-	_	_	_	-	0		03:15 PM	0	175	-	-	363		VUI 1036
38	03:30 PM	0	0 0	0	0		0	0 0	0	0	0 0	0 0	0 0	0	0 0	0	0 0	03:30 PM	0	339	12 20	176 350	709		
39	03:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	03:45 PM	0	539 537	34	562	1133		
40	03.43 PM 04:00 PM	0		0	0		-	_	0	7	0	U E	0	7	-	0	1	04:00 PM		734		802	1580		
41		0	0 0	0	0	0	165 158	10 6	0	/	0	⊃ ⁄1	1	4	169 170	0	0	04:00 PM	0 0	734 761	44 41	802 834	1636		
42	04:15 PM 04:30 PM	0	0	0	0	0	185	13	0	10	0	4	2	5	207	0	0	04:15 PM	0	803	41 45	834 810	1658		
43	04:30 PM 04:45 PM	0	0	0	0		190	13 7	1	7	0	4 2	2	3	237	0	2	04:45 PM	0			765	1603		
44	04:45 PM 05:00 PM	0	0	0	0		190	, 11	0	6	0	3	2	8	200	0	0	05:00 PM	0	798 784	40 42	674	1503		
45	05:00 PM 05:15 PM	0	0	0	0		191	9	0	3	0	3 9	1	9	141	0	0	U3.00 PIVI	U	704	42	0/4	1300	,	
46	05:15 PM 05:30 PM			0	0	_	185	8	2	6	0	9 2	0	6	161	0	_								
47	05:30 PM 05:45 PM	0	0 0	0	0	0	171	8 12	0	3	0	3 9	3	10	139	0	0 2								
48	05.45 FIVI	U	U	U	U	U	1/1	12	U		U	<u> </u>	<u> </u>	1 10	133	<u> </u>								_	



Computations - AM Peak Hour Vols

Project: 58036.00

Calculated by: ELQ

Checked by: JC

Date: 1/6/2020

design year 1: 2020 design year 2: 2025

Build Year Growth Factor: 1.03

Enter: 4 Exit: 7

	Unadjusted Data		110 Riverside Ave Trip Generation	2020 AM No Build	Trip Generation
* underlined roadway is N/S	1: Hillside Terrace West / Site Driveway		1: Hillside Terrace West / Site Driveway	1: Hillside Terrace West / Site Driveway	1: Hillside Terrace West / Site Driveway
	EB WB NB SB		EB WB NB SB	EB WB NB SB	EB WB NB SB
1	L		L	L 0 0 0 0	L 4
Hillside Terrace West / Site Driveway	T 4 5		Т	T 0 0 4 5	T
	R 9	same as	R 0	R 0 0 0 9	R 7 11
	Enter 0 0 4 5 9	PM	Enter 0 0 0 0 0	Enter 0 0 4 5 9	Enter 0 7 0 4 11
	Exit 0 0 4 5 9		Exit 0 0 0 0	Exit 0 0 4 5 9	Exit 4 0 7 0 11
	% Trucks		% Trucks	% Trucks 0%	% Trucks
	Peds PHF		Peds 0 0 0 PHF	Peds 0 0 0 PHF	Peds 0 0 0 PHF
	Peak Hour	Total Adjust: 1.015	Peak Hour	Peak Hour	Peak Hour
	2: Hillside Terrace West / Riverside Ave		2: Hillside Terrace West / Riverside Ave	2: Hillside Terrace West / Riverside Ave	2: Hillside Terrace West / Riverside Ave
	EB WB NB SB		EB WB NB SB	EB WB NB SB	EB WB NB SB
2	L 0 0 4 0		L	L 0 0 4 0	L 2 7
Hillside Terrace West / Riverside Ave	T 565 676 0 0		T 2 8	T 576 694 0 0	T
Tuesday, July 16, 2019	R 5 1 0 0 1251	same as	R 10	R 5 1 0 0 1280	R 2 0 11
	Enter 570 677 4 0 1251	PM	Enter 2 8 0 0 10	Enter 581 695 4 0 1280	Enter 2 2 7 0 11
	Exit 565 680 1 5 1251		Exit 2 8 0 0 10	Exit 576 698 1 5 1280	Exit 0 7 0 4 11
	% Trucks 3% 4% 0% 0%		% Trucks	% Trucks 0%	% Trucks
	Peds 0 0 3 0 PHF		Peds PHF	Peds 0 0 3 0 PHF	Peds PHF
	Peak Hour	Total Adjust: 1.015	Peak Hour	Peak Hour	Peak Hour
	3: Hillside Terrace East / Riverside Ave		3: Hillside Terrace East / Riverside Ave	3: Hillside Terrace East / Riverside Ave	3: Hillside Terrace East / Riverside Ave
	EB WB NB SB		EB WB NB SB	EB WB NB SB	EB WB NB SB
3	L 0 7 26 0		L	L 0 7 26 0	L
Hillside Terrace East / Riverside Ave	T 562 651 0 0		T 2 8	T 572 669 0 0	Т 0 2
Tuesday, July 16, 2019	R 11 0 42 0 1299	same as	R 10	R 11 0 43 0 1329	R 2
7:30 - 8:30 AM	Enter 573 658 68 0 1299	PM	Enter 2 8 0 0 10	Enter 584 676 69 0 1329	Enter 0 2 0 0 2
	Exit 604 677 0 18 1299		Exit 2 8 0 0 10	Exit 615 695 0 18 1329	Exit 0 2 0 0 2
	% Trucks 2% 2% 1% 0%		% Trucks	% Trucks	% Trucks
	Peds 2 7 3 0 PHF		Peds PHF	Peds 2 7 3 0 PHF	Peds PHF
	Peak Hour	Total Adjust: 1.015	Peak Hour	Peak Hour	Peak Hour
	<u> </u>				



Computations - AM Peak Hour Vols

 Project: 58036.00
 Location: Burlington

 Calculated by: ELQ
 Date: 43810

 Checked by: JC
 Date: 43836

		202	20 AM B	uild				2025	AM No	Build			2025 AM B	uild	
* underlined roadway is N/S	1: Hillsi	de Terrace W	/est / Site [Driveway			1: Hillsic	de Terrace W	/est / Site [Priveway			1: Hillside Terrace West /	Site Drive	way
		EB	WB	NB	SB	_	_	EB	WB	NB	SB	_	EB WB NE	3 SB	
1	L	0	0	0	4		L	0	0	0	0		L 0 0 0	4	
Hillside Terrace West / Site Driveway	Т	0	0	4	5		Т	0	0	4	5		T 0 0 4	5	
	R	0	7	0	0	20	R	0	0	0	0	9	R 0 7 0	0	20
	Enter	0	7	4	9	20	Enter	0	0	4	5	9	Enter 0 7 4	9	20
	Exit	4	0	11	5	20	Exit	0	0	4	5	9	Exit 4 0 11		20
	% Trucks	0%	0%	0%	0%		% Trucks	0%	0%	0%	0%			0%	
	Peds	0	0	0	0	PHF	Peds	0	0	0	0	PHF	Peds 0 0 0	0	PHF
	Peak Hour						Peak Hour						Peak Hour		
	2: Hillsi	de Terrace W	,				2: Hillsic	de Terrace W					2: Hillside Terrace West /		Ave
		EB	WB	NB	SB		-	EB	WB	NB	SB		EB WB NE		1
2	L	0	2	11	0		L	0	0	4	0		L 0 2 11		
Hillside Terrace West / Riverside Ave	Т	576	694	0	0		Т	593	715	0	0		T 593 715 0	-	
Tuesday, July 16, 2019	R	7	1	0	0	1291	R	5	1	0	0	1318	R 7 1 0	0	1329
	Enter	582	697	11	0	1291	Enter	598	716	4	0	1318	Enter 600 718 11		1329
	Exit	576	705	1	9	1291	Exit	593	719	1	5	1318	Exit 593 726 1	9	1329
	% Trucks		0%	0%	0%		% Trucks	0%	0%	0%	0%			0%	
	Peds	0	0	3	0	PHF	Peds	0	0	3	0	PHF	Peds 0 0 3	0	PHF
	Peak Hour						Peak Hour						Peak Hour		
	3: Hillsi	de Terrace E					3: Hillsic	de Terrace Ea					3: Hillside Terrace East /		ve
		EB	WB	NB	SB		F	EB	WB	NB	SB	-	EB WB NE		1
3	L	0	7	26	0		L	0	7	27	0		L 0 7 27		
Hillside Terrace East / Riverside Ave		572	671	0	0		'	590	689	0	0		T 590 691 0	-	
Tuesday, July 16, 2019	R	11	0	43	0	1331	R	12	0	44	0	1368	R 12 0 44		1371
7:30 - 8:30 AM	Enter	584	678	69	0	1331	Enter	601	696	71	0	1368	Enter 601 698 71		1371
	Exit	615	697	0	18	1331	Exit	634	716	0	19	1368	Exit 634 718 0		1371
	% Trucks	0%	0%	0%	0%	l	% Trucks	0%	0%	0%	0%			0%	
	Peds	2	7	3	0	PHF	Peds	2	/	3	0	PHF	Peds 2 7 3	0	PHF
	Peak Hour						Peak Hour						Peak Hour		



Computations - PM Peak Hour Vols

Project: 58036.00

Calculated by: ELQ

Checked by: IC

Location: Burlington, VT
Date: 12/11/19
Date: 1/6/20

Design Year 1: 2020 Design Year 2: 2025

Build Year Growth Factor: 1.03



	Unadjusted Data		110 Riverside Ave Trip Generation	2020 PM No Build	Trip Generation
* underlined roadway is N/S	1: Hillside Terrace West / Site Driveway		1: Hillside Terrace West / Site Driveway	1: Hillside Terrace West / Site Driveway	1: Hillside Terrace West / Site Driveway
	EB WB NB SB		EB WB NB SB	EB WB NB SB	EB WB NB SB
1	L		L	L 0 0 0 0	L 9
Hillside Terrace West / Site Driveway	T 10 5		Т	T 0 0 10 5	Т
	R 15	same as	R O	R 0 0 0 0 15	R 8 17
	Enter 0 0 10 5 15	below	Enter 0 0 0 0 0	Enter 0 0 10 5 15	Enter 0 8 0 9 17
	Exit 0 0 10 5 15		Exit 0 0 0 0	Exit 0 0 10 5 15	Exit 9 0 8 0 17
	% Trucks		% Trucks	% Trucks 0%	% Trucks
	Peds PHF		Peds 0 0 0 PHF	Peds 0 0 0 PHF	Peds 0 0 0 PHF
		Total Adjust: 1.015	Peak Hour	Peak Hour	Peak Hour
	2: Hillside Terrace West / Riverside Ave		2: Hillside Terrace West / Riverside Ave	2: Hillside Terrace West / Riverside Ave	2: Hillside Terrace West / Riverside Ave
	EB WB NB SB		EB WB NB SB	EB WB NB SB	EB WB NB SB
2	L 0 0 3 0		L	L 0 0 3 0	L 4 3
Hillside Terrace West / Riverside Ave	T 896 776 0 0		T 8 5	T 918 793 0 0	Т
Tuesday, July 16, 2019	R 5 0 7 0 1687	same as	R 13	R 5 0 7 0 1725	R 5 5 17
	Enter 901 776 10 0 1687	below	Enter 8 5 0 0 13	Enter 923 793 10 0 1725	Enter 5 4 8 0 17
	Exit 903 779 0 5 1687		Exit 8 5 0 0 13	Exit 925 796 0 5 1725	Exit 5 3 0 9 17
	% Trucks 0% 0% 0% 0%		% Trucks	% Trucks 0%	% Trucks
	Peds 0 0 11 0 PHF		Peds PHF	Peds 0 0 11 0 PHF	Peds PHF
		Total Adjust: 1.015	Peak Hour	Peak Hour	Peak Hour
	3: Hillside Terrace East / Riverside Ave		3: Hillside Terrace East / Riverside Ave	3: Hillside Terrace East / Riverside Ave	3: Hillside Terrace East / Riverside Ave
	EB WB NB SB	ATR ID: D156	EB WB NB SB	EB WB NB SB	EB WB NB SB
3		TR/CTC AADT: 15923	L	L 0 41 19 0	L
Hillside Terrace East / Riverside Ave	T 785 763 0 0		T 8 5	T 805 780 0 0	T 5 4
Tuesday, July 16, 2019	R 25 0 26 0 1658		R 13	R 25 0 26 0 1696	R 9
4:30 - 5:30 PM		V (Red Book): 1600	Enter 8 5 0 0 13	Enter 830 820 46 0 1696	Enter 5 4 0 0 9
	Exit 811 782 0 65 1658	Corr. Count: 1592	Exit 8 5 0 0 13	Exit 831 799 0 66 1696	Exit 5 4 0 0 9
	% Trucks 1% 1% 0% 0%	DHV Adjust: 1.01	% Trucks	% Trucks 1% 1% 0% 0%	% Trucks
	Peds 2 1 7 0 PHF T	MC YR adjust: 1.01	Peds PHF	Peds 2 1 7 0 PHF	Peds PHF
	Peak Hour	Total Adjust: 1.015	Peak Hour	Peak Hour	Peak Hour



Computations - PM Peak Hour Vols

Project: 58036.00

Calculated by: ELQ

Date: 1/6/20

Peds	SB 9 5 0 14 5 0% 0 0	32 32 32 32 PHF
1 0 0 0 0 0 0 0 0 0	9 5 0 14 5 6 0% 0	32 32
Hillside Terrace West / Site Drive File	5 0 14 5 6 0% 0	32 32
R	0 14 5 6 0% 0	32 32
Enter O B 10 14 32 Enter O O 10 5 16 Enter O B 10 14 14 14 14 14 14 14	14 5 6 0% 0	32 32
Exit 9	5 6 0% 0 e SB	32
%Truck	6 0% 0 e SB	
Peds Peak Hour	0 e SB	PHF
Peak Hour Peak Hour Pe	e SB	PHF
2: Hillside Terrace West / Riverside Ave 2: Hillside Terrace Wes	SB	
Fig. WB NB SB Fig. NB SB Fig. NB SB Fig. Fig. NB SB Fig. Fig. NB SB Fig. Fig. NB SB Fig. Fig. Fig. NB SB Fig. Fig. Fig. NB NB SB Fig. Fig. Fig. Fig. NB NB SB Fig.	SB	
L 0 4 6 0 0 1 1 1 1 1 1 1 1		
Hillside Terrace West / Riverside T 918 793 0 0 0 1742 R 5 0 7 0 1777 R 10 0 12 0 1742 R 5 0 7 0 1777 R 1777 R 1777 R 1777 1777 R		
Tuesday, July 16, 2019 R 10 0 12 0 1742 Enter 927 797 18 0 1742 Exit 929 799 0 14 1742 Exit 929 820 0 5 177 Exit 929 799 0 14 1742 Exit 929 820 0 5 177 Exit 929 821 18 %Trucks 0% 0% 0% 0% 0% 0% 0% 0% 0% 0% 0% 0% 0%	0	1
Enter 927 797 18 0 1742 Enter 950 816 10 0 1777 Enter 955 821 18 Exit 929 799 0 14 1742 Exit 952 820 0 5 1777 Exit 957 823 0 %Trucks 0% 0% 0% 0% 0% 0% 0% 0% 0% 0% 0% 0% 0%	0	1
Exit 929 799 0 14 1742 Exit 952 820 0 5 1777 Exit 957 823 0 % Trucks 0% <td></td> <td>1794</td>		1794
% Trucks 0% 0% 0% % Trucks 0% 0% 0% 0% 7 Trucks 0% <td></td> <td>1794</td>		1794
Peds 0 0 11 0 PHF Peds 0 0 0 PHF Peds 0 0 11 Peak Hour 3: Hillside Terrace East / Riverside Ave 3: Hillside Terrace East / Rive		1794
Peak Hour Peak Hour Peak Hour Peak Hour At Hour Peak Hou	6 0%	1
3: Hillside Terrace East / Riverside Ave 3: Hillside Terrace East / Riverside Ave 3: Hillside Terrace East / Riverside Ave	0	PHF
,,,,,,,,		
EB WB NB SB EB WB NB SB EB WB NB	SB	
3 L 0 41 19 0 L 0 42 20 0 L 0 42 20	0	i
<u>Hillside Terrace East</u> / Riverside / T 809 784 0 0 T 829 803 0 0 T 834 807 0	0	1
Tuesday, July 16, 2019 R 25 0 26 0 1705 R 26 0 27 0 1747 R 26 0 27		1756
4:30 - 5:30 PM Enter 835 824 46 0 1705 Enter 855 845 47 0 1747 Enter 860 849 47		1756
Exit 836 803 0 66 1705 Exit 856 823 0 68 1747 Exit 861 827 0		1756
	6 0%	l .
Peds 2 1 7 0 PHF Peds PHF Peds		PHF
Peak Hour Peak Hour Peak Hour		




Appendix B

Crash Data

Riverside Avenue Crash Data





iectl	

Crash Date	Address	Crash Type	Collision Direction	Weather	Intersection With	Road Characteristics	Surface Condition
121245 April 4, 2014, 8:28 AM	US-7 Riverside Ave	Property Damage Only	Other - Explain in Narrative	Clear	Hildred Dr	Four-way Intersection	Dry
114907 June 6, 2014, 4:57 PM	Riverside Ave	Property Damage Only	Rear End	Clear	Hillside Ter	T - Intersection	Dry
115699 June 16, 2014, 4:36 PM	Riverside Ave	Property Damage Only	Rear End	Clear	Hillside Terr	Not at a Junction	Dry
112252 July 14, 2014, 5:31 PM	US-7 Riverside Ave	Property Damage Only	Rear End	Rain	Hildred Dr	T - Intersection	Wet
115238 August 22, 2014, 5:51 PM	Riverside Ave	Injury	Rear End	Clear	Hillside Terr	T - Intersection	Dry
114077 November 2, 2014, 3:29 PM	Hillside Ter	Property Damage Only	No Turns, Thru moves only, Broadside ^<	Clear	Riverside Ave	T - Intersection	Dry
128919 March 11, 2015, 3:51 PM	US-7 Riverside Ave	Property Damage Only	No Turns, Thru moves only, Broadside ^<	Clear	Hillside Ter	T - Intersection	Dry
135032 July 8, 2015, 1:10 PM	Riverside Ave	Property Damage Only	Rear End	Clear	Hillside Drive	Not at a Junction	Dry
135866 July 27, 2015, 5:51 PM	US-7 Riverside Ave	Injury	Rear End	Clear	Hillside Ter	Not at a Junction	Dry
135855 July 28, 2015, 5:31 PM	Riverside Ave	Property Damage Only	Rear End	Clear	Hillside Terr	Not at a Junction	Dry
136731 August 18, 2015, 8:48 AM	Riverside Ave	Injury	No Turns, Thru moves only, Broadside ^<	Clear	Hillside Ter	Driveway	Dry
137378 September 1, 2015, 4:46 PM	Riverside Ave	Injury	No Turns, Thru moves only, Broadside ^<	Clear	Hillside Terr	Driveway	Dry
738237 December 29, 2015, 12:52 PM	Hillside Ter	Property Damage Only	Right Turn and Thru, Head On v^	Freezing Precipitation	r Riverside Ave	T - Intersection	Snow
738909 April 1, 2016, 7:09 PM	Riverside Ave	Injury	Left Turn and Thru, Angle Broadside>v	Clear	Hillside Ter	T - Intersection	Dry
731856 April 8, 2016, 12:15 PM	Riverside Ave	Property Damage Only	Left Turn and Thru, Angle Broadside>v	Cloudy	Hillside Terr	T - Intersection	Wet
721369 May 13, 2016, 11:02 AM	Hillside Terr	Injury	No Turns, Thru moves only, Broadside ^<	Rain	Riverside Ave	T - Intersection	Wet
809492 August 7, 2017, 4:25 PM	Riverside Ave	Property Damage Only	Opp Direction Sideswipe	Rain	Hillside Ter	Not at a Junction	Wet
1861094 August 31, 2017, 4:53 PM	Riverside Ave	Property Damage Only	Left Turn and Thru, Head On ^v	Clear	Hillside Ave	T - Intersection	Dry
1859927 September 14, 2017, 1:55 PM	Riverside Ave	Property Damage Only	Rear End	Cloudy	Hillside Ter	Parking Lot	Dry
810819 November 9, 2017, 12:35 AM	Riverside Ave	Injury		Clear	Hillside Ter	Not at a Junction	Dry
1861549 December 6, 2017, 4:28 PM	Riverside Ave	Property Damage Only	Rear End	Clear	Hillside Terr	T - Intersection	Dry
1856443 May 12, 2018, 5:17 PM	Riverside Ave	Injury	Right Turn and Thru, Broadside ^<	Clear	Hillside Dr	Driveway	Dry
1856858 July 31, 2018, 4:46 PM	Riverside Ave	Property Damage Only			Hillside Terr		
1856991 August 8, 2018, 7:45 AM	Riverside Ave	Property Damage Only			Hillside Ter		
1856659 September 2, 2018, 4:28 PM	Riverside Ave	Property Damage Only	Rear End	Clear	Hillside Ter	Not at a Junction	Dry

Crashes in Project Area.xlsx



Appendix C

Trip Generation Summary

Trip Generation - Riverside Independent Living Facility

Total Site generated trips (not accounting for internal, pass-by, or diverted trips)

				directio	nal dist.		aver	age			ession	# tri _l			
Code Land	d Use	Size	Unit	% enter	% exit	# studies	Avg Rate	Std Dev.	Total by Avg	r²	total by Eq'n	Method Chosen	Total Trips	Entering	Exiting
1	2	3	4	5	6	7	8	9	10	11	12	13	14		
252 6		60	5 - 111 - 11 - 11	250/	650/	l 44	0.20	0.05	42	0.00	42	B	42		0
252 Senio	or Adult Housing - Attached	60	Dwelling Units	35%	65%	11	0.20	0.05	12	0.98	12	Regression	12	4	8

AM Peak Hour Total Site Trips: 12 4

				PM PK H	R OF ADJA	CENT ST	REET TRAF				
direction	nal dist.		aver	age			ession	# tri _l			
% enter	% exit	# studies	Avg Rate	Std Dev.	Total by Avg	r²	total by Eq'n	Method Chosen	Total Trips	Entering	Exiting
15	16	17	18	19	20	21	22	23	24		
55%	45%	11	0.26	0.08	16	0.96	17	Regression	17	9	8

PM Peak Hour Total Site Trips: 17 9



Appendix D

110 Riverside Avenue Traffic Impact Analysis

Introduction

The purpose of this Traffic Impact Analysis is to update previously identified potential traffic impacts relating to the proposed construction of a 57 unit apartment building on Riverside Avenue in Burlington, Vermont, A Traffic Impact Report was conducted in 2013 for the project, which has not yet been constructed. The project is located on the south side of Riverside Avenue on the site of the former M&H Auto building. Figure 1: Location Map illustrates the property location in relation to the street network in the immediate area. Updates included a comparison of 2013 versus current traffic volume, an updated design hour capacity analysis, and updated crash analysis.




Figure 1: Location Map

Existing Conditions

Riverside Avenue is classified by VTrans as an Urban Principal Arterial, and is also known as US Route 2/7 in this location. For the purpose of this report, Riverside Ave will be referred to as running east-west. There is a single lane of travel, plus a bike lane, in each direction. The speed limit is posted at 25 miles per hour (mph) and there is an advisory

speed curve warning 25 mph posted in advance of the curve in both directions. A shared-use path is located on the north side of the road, and a concrete sidewalk runs along the project's frontage on the south side of the road from the west, terminating and the eastern property boundary. An annual average daily traffic (AADT) volume of 15,900 vehicles per day was recorded in 2018 at automatic traffic recorder (ATR) station S6D156, located 0.5 miles south (or west) of Colchester Avenue. The base AADT used in the 2013 traffic study was 15,000 vpd.





Figure 2: Riverside Ave Traffic History

Sisters and Brothers Investment Group

Burlington, Vermont



Proposed trip distribution is based primarily on analogy to this short count. Projected traffic volumes in front of the site during morning and evening peak traffic hours are illustrated in the diagrams below.

Figure 3: AM Peak Traffic Distribution




Figure 4: PM Peak Traffic Distribution

Level of Service Analysis – Project Driveway

A capacity analysis was performed on the intersection of the project driveway with Riverside Avenue. Because the PM Peak has a significantly higher hourly traffic volume than the AM peak (approx. 1900 vph PM Peak vs during 1150 vph AM Peak), only the PM Peak was analyzed. For analysis purposes, the eastern driveway was modeled with all of the traffic utilizing that entrance. It is anticipated that some of the right turning movements (ingress only) will take place at the western driveway. Level of Service (LOS) was calculated for the HCM2010 methodology. The HCM levels of service used in the analysis are based on control delay of critical movements and are summarized in the table below.

Sisters and Brothers Investment Group

Burlington, Vermont

The table below identifies the northbound Riverside Avenue approach to the Barrett Street intersection for current traffic conditions, as identified in the Scoping Study. The distance between the intersection and the easternmost project driveway is approximately 750 feet. There are no conflicting crossings or driveways that are affected by this existing traffic queue, aside from the trailhead parking on the north side of Riverside Ave.

Table 4: Existing Conditions - Peak Hour Analysis

	Northbound Riverside Ave (through movement)
Traffic Volume	914 veh
Delay	65.6 s
LOS	Е
Queue – 95 th Percentile	572 ft
Queue – 50 th Percentile	422 ft
Distance to new Drive	750 ft

The increase in traffic of 13 total trips at this intersection during the PM Peak represents less than 1% of total traffic, which is smaller than the limits of daily fluctuation in volume experienced by the intersection system.

Crash History – Project Driveway

The crash history for within a 0.2 mile (approximately 1000 ft) section of Riverside Avenue, centered on the proposed project was reviewed using the VTrans Crash Query. According to this listing, 13 crashes occurred during the five-year period between 2014 and 2018. A crash rate of 2.280 crashes per million vehicle miles (Cr/MVM) was calculated for the corridor. The critical rate calculated for Urban Principal Arterials in Vermont was noted as 7.551 Cr/MVM in the most recent Summary of Statewide Average Crash Rates, resulting in the section not being considered a high crash location.

While this section of the Riverside Ave Corridor would not be considered a High Crash Location, the adjacent intersection system includes the Colchester Ave/Barrett Street intersection, which is identified by VTrans as a High Crash Location.

Sight Distance

Sight distance measurements were taken on Riverside Avenue at the two driveway locations. The table below outlines the measured sight distance and the AASHTO recommended intersection and stopping sight distances.

Table 5: Sight Distance

		Measured	Intersection :	Intersection Sight Distance ¹						
		3/6/2013	Left from Stop	Right From Stop	Sight Distance					
East	To East	342 ft	280 ft	_	155 ft					
Driveway	To West	312* ft	-	240 ft	155 ft					
West	To East	317 ft	280 ft	_	155 ft					
Driveway	To West	676 ft	-	240 ft	155 ft					

¹ Table 9-6, 9-8; A Policy on the Geometric Design of Highways and Streets, 2011, AASHTO.

Sisters and Brothers Investment Group

Burlington, Vermont

intersection), and added striping for the inclusion of bicycle lanes. Several other non-pedestrian intersection improvements are recommended, including new pavement markings, protected left phase for southbound Colchester Avenue, right-turn arrow for southbound right turns, and advance lane designation signs.

The proposed project has a current Act 250 Permit (4C1282, 4C0282-1) in which they have a condition to pay a proportional fair-share monetary contribution toward the Colchester Ave/Riverside Ave/Barrett Street intersection improvements. Their contribution was calculated based on the projects proportion of overall traffic at the intersection and is in the amount of \$15,260, which is to be paid prior to commencement of construction. The Burlington City Council endorsed the Short Term and 4-Way intersection improvement alternatives outlined in the report in the spring of 2019 and the City is currently pursuing implementation of these measures.

Summary of Findings

Based on review and analysis of the existing and proposed traffic conditions, the following conclusions are presented.

- Sisters and Brothers Investment Group is proposing the construction of a 57 unit
 apartment building to be located at 110 Riverside Avenue in Burlington. The property is
 located on the south side of the road, approximately 0.15 miles west of Colchester
 Avenue.
- 2. The project will have direct access to Riverside Avenue. The eastern driveway will allow both ingress and egress, while the west driveway movements will be limited to right-in only, for direct access to the parking garage. The new driveways will replace two existing curb cuts.
- 3. According to ITE Trip Generation, 10th Edition, the project is expected to generate approximately 21 new trips during the AM peak, with 5 entering and 16 exiting. During the afternoon peak, the project is estimated to generate 25 trips, 15 entering and 10 exiting. The project is located on a bus line.
- 4. The additional 25 trips on the road resulting from the proposed project represents 1.5% of total PM design hour traffic on Riverside Avenue. The proposed trip distribution will add 13 trips to the adjacent Riverside/Barrett St intersection, an increase of just over 0.5%.
- 5. Level of service on Riverside Ave at the new driveway intersection is calculated as a B during the PM peak hours. Level of service at the project access will be an E (40 seconds delay) during the PM peak hour. Excessive queuing is not anticipated at the project driveway due to the low number of exiting vehicles.
- 6. It is estimated that the proposed project will add approximately 5 vehicles to northbound Riverside Ave at the Barrett Street/Colchester Ave intersection, and 6 vehicle trips to southbound Riverside Ave during the PM Peak. This increase is just over



Appendix E

Intersection Capacity Analysis

	-	•	•	←	•	~
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	f			4	¥#	
Traffic Volume (veh/h)	576	5	0	694	4	0
Future Volume (Veh/h)	576	5	0	694	4	0
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	576	5	0	694	4	0
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (ft)	1288			325		
pX, platoon unblocked					0.78	
vC, conflicting volume			581		1272	578
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol			581		1207	578
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)						
tF (s)			2.2		3.5	3.3
p0 queue free %			100		97	100
cM capacity (veh/h)			993		157	515
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	581	694	4			
Volume Left	0	0	4			
Volume Right	5	0	0			
cSH	1700	993	157			
Volume to Capacity	0.34	0.00	0.03			
Queue Length 95th (ft)	0.54	0.00	2			
Control Delay (s)	0.0	0.0	28.5			
Lane LOS	0.0	0.0	20.5 D			
Approach Delay (s)	0.0	0.0	28.5			
Approach LOS	0.0	0.0	20.5 D			
••			U			
Intersection Summary			0.4			
Average Delay			0.1			
Intersection Capacity Utiliz	ation		46.5%	IC	U Level c	t Service
Analysis Period (min)			15			

	-	\rightarrow	•	•	•	<i>></i>	
Movement	EBT	EBR	WBL	WBT	NBL	NBR	
Lane Configurations	1		*		*/f		
Traffic Volume (vph)	572	11	7	669	26	43	
Future Volume (vph)	572	11	7	669	26	43	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost time (s)	5.0		5.0	5.0	4.0		
Lane Util. Factor	1.00		1.00	1.00	1.00		
Frt	1.00		1.00	1.00	0.92		
Flt Protected	1.00		0.95	1.00	0.98		
Satd. Flow (prot)	1858		1770	1863	1674		
Flt Permitted	1.00		0.36	1.00	0.98		
Satd. Flow (perm)	1858		670	1863	1674		
Peak-hour factor, PHF	1.00	1.00	1.00	1.00	1.00	1.00	
Adj. Flow (vph)	572	11	7	669	26	43	
RTOR Reduction (vph)	1	0	0	0	35	0	
Lane Group Flow (vph)	582	0	7	669	34	0	
Turn Type	NA		Perm	NA	Prot		
Protected Phases	2			6	4		
Permitted Phases			6				
Actuated Green, G (s)	55.4		55.4	55.4	16.1		
Effective Green, g (s)	55.4		55.4	55.4	16.1		
Actuated g/C Ratio	0.63		0.63	0.63	0.18		
Clearance Time (s)	5.0		5.0	5.0	4.0		
Vehicle Extension (s)	3.0		3.0	3.0	3.0		
Lane Grp Cap (vph)	1169		421	1172	306		
v/s Ratio Prot	0.31			c0.36	c0.02		
v/s Ratio Perm			0.01				
v/c Ratio	0.50		0.02	0.57	0.11		
Uniform Delay, d1	8.8		6.1	9.4	30.0		
Progression Factor	1.00		1.00	1.00	1.00		
Incremental Delay, d2	1.5		0.0	0.7	0.7		
Delay (s)	10.3		6.1	10.1	30.7		
Level of Service	В		Α	В	С		
Approach Delay (s)	10.3			10.1	30.7		
Approach LOS	В			В	С		
Intersection Summary							
HCM 2000 Control Delay			11.2	H	CM 2000	Level of Service	В
HCM 2000 Volume to Capa	city ratio		0.45				
Actuated Cycle Length (s)			88.0		um of lost		14.0
Intersection Capacity Utiliza	ation		46.8%	IC	U Level o	f Service	Α
Analysis Period (min)			15				

c Critical Lane Group

	-	•	•	←	•	/
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	ĵ.			4	W	
Traffic Volume (veh/h)	918	5	0	793	3	7
Future Volume (Veh/h)	918	5	0	793	3	7
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	918	5	0	793	3	7
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (ft)	1288			325		
pX, platoon unblocked				3_3	0.71	
vC, conflicting volume			923		1714	920
vC1, stage 1 conf vol			7_7			
vC2, stage 2 conf vol						
vCu, unblocked vol			923		1802	920
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					<u> </u>	<u> </u>
tF (s)			2.2		3.5	3.3
p0 queue free %			100		95	98
cM capacity (veh/h)			740		62	328
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	923	793	10			
Volume Left	0	0	3			
Volume Right	5	0	7			
cSH	1700	740	143			
Volume to Capacity	0.54	0.00	0.07			
Queue Length 95th (ft)	0.01	0.00	6			
Control Delay (s)	0.0	0.0	32.0			
Lane LOS	0.0	0.0	D D			
Approach Delay (s)	0.0	0.0	32.0			
Approach LOS	0.0	0.0	D D			
• •						
Intersection Summary			0.0			
Average Delay			0.2	10	111	.f Camilla
Intersection Capacity Utiliz	zation		58.6%	IC	U Level c	or Service
Analysis Period (min)			15			

	-	•	•	←	1	/		
Movement	EBT	EBR	WBL	WBT	NBL	NBR		
Lane Configurations	1>		ች	†	W			
Traffic Volume (vph)	805	25	41	780	19	26		
Future Volume (vph)	805	25	41	780	19	26		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900		
Total Lost time (s)	5.0		5.0	5.0	4.0	1000		
Lane Util. Factor	1.00		1.00	1.00	1.00			
Frt	1.00		1.00	1.00	0.92			
Flt Protected	1.00		0.95	1.00	0.98			
Satd. Flow (prot)	1855		1770	1863	1682			
FIt Permitted	1.00		0.21	1.00	0.98			
Satd. Flow (perm)	1855		386	1863	1682			
Peak-hour factor, PHF	1.00	1.00	1.00	1.00	1.00	1.00		
Adj. Flow (vph)	805	25	41	780	19	26		
RTOR Reduction (vph)	1	0	0	0	21	0		
Lane Group Flow (vph)	829	0	41	780	24	0		
Turn Type	NA		Perm	NA	Prot			
Protected Phases	2		1 01111	6	4			
Permitted Phases			6		'			
Actuated Green, G (s)	55.4		55.4	55.4	16.1			
Effective Green, g (s)	55.4		55.4	55.4	16.1			
Actuated g/C Ratio	0.63		0.63	0.63	0.18			
Clearance Time (s)	5.0		5.0	5.0	4.0			
Vehicle Extension (s)	3.0		3.0	3.0	3.0			
Lane Grp Cap (vph)	1167		243	1172	307			
v/s Ratio Prot	c0.45		210	0.42	c0.01			
v/s Ratio Perm	00.10		0.11	0.12	00.01			
v/c Ratio	0.71		0.17	0.67	0.08			
Uniform Delay, d1	10.9		6.8	10.4	29.8			
Progression Factor	1.00		1.00	1.00	1.00			
Incremental Delay, d2	3.7		0.3	1.4	0.5			
Delay (s)	14.6		7.1	11.8	30.3			
Level of Service	В		Α	В	С			
Approach Delay (s)	14.6			11.6	30.3			
Approach LOS	В			В	С			
Intersection Summary								
HCM 2000 Control Delay			13.6	Н	CM 2000	Level of Service	В	
HCM 2000 Volume to Cap	acity ratio		0.55	- 11	OIVI 2000	LOVE OF OUR VICE	D	
Actuated Cycle Length (s)			88.0	Si	um of lost	time (s)	14.0	
Intersection Capacity Utiliz			54.7%		CU Level c	` '	A	
Analysis Period (min)			15	10			, ,	
Alialysis Fellou (IIIIII)			10					

	-	•	•	•	•	~
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	4			4	W	
Traffic Volume (veh/h)	576	7	2	694	11	0
Future Volume (Veh/h)	576	7	2	694	11	0
Sign Control	Free	•	_	Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	576	7	2	694	11	0
Pedestrians	010	,		00+	- ''	<u> </u>
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)	NOTIE			NOHE		
	1288			325		
Upstream signal (ft)	1200			323	0.77	
pX, platoon unblocked			583		1278	580
vC, conflicting volume			203		1270	200
vC1, stage 1 conf vol						
vC2, stage 2 conf vol			E02		1010	E00
vCu, unblocked vol			583		1213	580
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)			0.0		2.5	2.2
tF (s)			2.2		3.5	3.3
p0 queue free %			100		93	100
cM capacity (veh/h)			991		155	515
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	583	696	11			
Volume Left	0	2	11			
Volume Right	7	0	0			
cSH	1700	991	155			
Volume to Capacity	0.34	0.00	0.07			
Queue Length 95th (ft)	0	0	6			
Control Delay (s)	0.0	0.1	30.0			
Lane LOS		Α	D			
Approach Delay (s)	0.0	0.1	30.0			
Approach LOS			D			
Intersection Summary						
Average Delay			0.3			
Intersection Capacity Utiliza	ation		48.1%	IC	U Level c	f Service
Analysis Period (min)			15			

	-	•	•	←	1	/		
Movement	EBT	EBR	WBL	WBT	NBL	NBR		
Lane Configurations	1 2		ሻ		W			
Traffic Volume (vph)	572	11	7	671	26	43		
Future Volume (vph)	572	11	7	671	26	43		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900		
Total Lost time (s)	5.0		5.0	5.0	4.0			
Lane Util. Factor	1.00		1.00	1.00	1.00			
Frt	1.00		1.00	1.00	0.92			
Flt Protected	1.00		0.95	1.00	0.98			
Satd. Flow (prot)	1858		1770	1863	1674			
Flt Permitted	1.00		0.36	1.00	0.98			
Satd. Flow (perm)	1858		670	1863	1674			
Peak-hour factor, PHF	1.00	1.00	1.00	1.00	1.00	1.00		
Adj. Flow (vph)	572	11	7	671	26	43		
RTOR Reduction (vph)	1	0	0	0	35	0		
Lane Group Flow (vph)	582	0	7	671	34	0		
Turn Type	NA		Perm	NA	Prot			
Protected Phases	2		1 01111	6	4			
Permitted Phases			6		'			
Actuated Green, G (s)	55.4		55.4	55.4	16.1			
Effective Green, g (s)	55.4		55.4	55.4	16.1			
Actuated g/C Ratio	0.63		0.63	0.63	0.18			
Clearance Time (s)	5.0		5.0	5.0	4.0			
Vehicle Extension (s)	3.0		3.0	3.0	3.0			
Lane Grp Cap (vph)	1169		421	1172	306			
v/s Ratio Prot	0.31		721	c0.36	c0.02			
v/s Ratio Perm	0.01		0.01	00.00	00.02			
v/c Ratio	0.50		0.02	0.57	0.11			
Uniform Delay, d1	8.8		6.1	9.4	30.0			
Progression Factor	1.00		1.00	1.00	1.00			
Incremental Delay, d2	1.5		0.0	0.7	0.7			
Delay (s)	10.3		6.1	10.1	30.7			
Level of Service	В		Α	В	C			
Approach Delay (s)	10.3		, ,	10.1	30.7			
Approach LOS	В			В	C			
Intersection Summary								
HCM 2000 Control Delay			11.3	Н	CM 2000	Level of Service	В	
HCM 2000 Volume to Cap	acity ratio		0.45		2 2000			
Actuated Cycle Length (s)			88.0	Si	um of lost	time (s)	14.0	
Intersection Capacity Utiliz			46.9%		CU Level c		Α	
Analysis Period (min)			15		. 5 _5.0.0	50	,,	
Critical Lana Croup			- 10					

c Critical Lane Group

	•	•	†	~	>	
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		f)			4
Traffic Volume (veh/h)	0	7	4	0	4	5
Future Volume (Veh/h)	0	7	4	0	4	5
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	0	7	4	0	4	5
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume	17	4			4	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	17	4			4	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	99			100	
cM capacity (veh/h)	999	1080			1618	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	7	4	9			
Volume Left	0	0	4			
Volume Right	7	0	0			
cSH	1080	1700	1618			
Volume to Capacity	0.01	0.00	0.00			
Queue Length 95th (ft)	0	0	0			
Control Delay (s)	8.4	0.0	3.2			
Lane LOS	Α		Α			
Approach Delay (s)	8.4	0.0	3.2			
Approach LOS	Α					
Intersection Summary						
Average Delay			4.4			
Intersection Capacity Utiliz	zation		13.8%	IC	U Level o	f Service
Analysis Period (min)			15			2211.00
rangolo i oriou (iliii)			10			

	-	\rightarrow	•	←	•	~
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	1>			4	W	
Traffic Volume (veh/h)	918	10	4	793	6	12
Future Volume (Veh/h)	918	10	4	793	6	12
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	918	10	4	793	6	12
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (ft)	1288			325		
pX, platoon unblocked					0.70	
vC, conflicting volume			928		1724	923
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol			928		1818	923
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)						
tF (s)			2.2		3.5	3.3
p0 queue free %			99		90	96
cM capacity (veh/h)			737		60	327
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	928	797	18			
Volume Left	0	4	6			
Volume Right	10	0	12			
cSH	1700	737	131			
Volume to Capacity	0.55	0.01	0.14			
Queue Length 95th (ft)	0	0	12			
Control Delay (s)	0.0	0.2	36.7			
Lane LOS		Α	Е			
Approach Delay (s)	0.0	0.2	36.7			
Approach LOS			Е			
Intersection Summary						
Average Delay			0.4			
Intersection Capacity Utiliza	ation		58.9%	IC	U Level o	f Service
Analysis Period (min)			15			

Movement		-	•	•	←	1	/		
Lane Configurations 1	Movement	EBT	EBR	WBL	WBT	NBL	NBR		
Traffic Volume (vph)									
Future Volume (vph)			25				26		
Ideal Flow (vphpl)									
Total Lost time (s) 5.0 5.0 5.0 4.0 Lane Util. Factor 1.00 1.00 1.00 1.00 Fit 1.00 1.00 1.00 1.00 0.92 Fit Protected 1.00 0.95 1.00 0.98 Satd. Flow (prot) 1855 1770 1863 1682 Fit Permitted 1.00 0.20 1.00 0.98 Satd. Flow (perm) 1855 381 1863 1682 Peak-hour factor, PHF 1.00 1.00 1.00 1.00 1.00 1.00 Adj. Flow (vph) 810 25 41 784 19 26 RTOR Reduction (vph) 1 0 0 0 21 0 Lane Group Flow (vph) 834 0 41 784 24 0 Furn Type NA Perm NA Prot Protected Phases 6 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 5.0 5.0 5.0 18 Clearance Time (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Vehicle Extension (s) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Prot c1.00 1.00 1.00 1.00 1.00 Incremental Delay, d1 11.0 6.8 10.4 29.8 Intersection Summary									
Lane Util. Factor 1.00 1.00 1.00 1.00 0.92 Fit 1.00 1.00 1.00 0.92 Fit Protected 1.00 0.95 1.00 0.98 Sald. Flow (prot) 1855 17770 1863 1682 Fit Permitted 1.00 0.20 1.00 0.98 Sald. Flow (perm) 1855 381 1863 1682 Feak-hour factor, PHF 1.00 1.00 1.00 1.00 1.00 1.00 1.00 Adj. Flow (vph) 810 25 41 784 19 26 RTOR Reduction (vph) 1 0 0 0 21 0 Lane Group Flow (vph) 834 0 41 784 24 0 Turn Type NA Perm NA Prot Protected Phases 2 6 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Actuated Green, G (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 V/s Ratio Prot 0.045 0.42 0.01 V/s Ratio Port 0.045 0.42 0.01 V/s Ratio Perm 0.11 V/c Ratio 0.71 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Intersection Summary									
Fit				1.00					
Satd. Flow (prot) 1855 1770 1863 1682 Filt Permitted 1.00 0.20 1.00 0.98 Satd. Flow (perm) 1855 381 1863 1682 Peak-hour factor, PHF 1.00 1.00 1.00 1.00 1.00 Adj. Flow (vph) 810 25 41 784 19 26 RTOR Reduction (vph) 1 0 0 0 21 0 Lane Group Flow (vph) 834 0 41 784 24 0 Turn Type NA Perm NA Prot Protected Phases 2 6 4 Permitted Phases 6 4 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 5.0 4.0 Veh									
Fit Permitted 1.00 0.20 1.00 0.98 Satd. Flow (perm) 1855 381 1863 1682 Peak-hour factor, PHF 1.00 1.00 1.00 1.00 1.00 1.00 Adj. Flow (vph) 810 25 41 784 19 26 RTOR Reduction (vph) 1 0 0 0 21 0 Lane Group Flow (vph) 834 0 41 784 24 0 Turn Type NA Perm NA Prot Protected Phases 2 6 4 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Perm 0.11 v/c Ratio 0.71 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Intersection Summary	Flt Protected	1.00		0.95	1.00	0.98			
Fit Permitted 1.00 0.20 1.00 0.98 Satd. Flow (perm) 1855 381 1863 1682 Peak-hour factor, PHF 1.00 1.00 1.00 1.00 1.00 1.00 Adj. Flow (vph) 810 25 41 784 19 26 RTOR Reduction (vph) 1 0 0 0 21 0 Lane Group Flow (vph) 834 0 41 784 24 0 Turn Type NA Perm NA Prot Protected Phases 2 6 4 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 V/s Ratio Prot 0.45 V/s Ratio Perm 0.11 V/c Ratio 0.71 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Approach LOS B B A B C Intersection Summary	Satd. Flow (prot)	1855		1770	1863	1682			
Peak-hour factor, PHF 1.00 1.00 1.00 1.00 1.00 1.00 Adj. Flow (vph) 810 25 41 784 19 26 RTOR Reduction (vph) 1 0 0 0 21 0 Lane Group Flow (vph) 834 0 41 784 24 0 Turn Type NA Perm NA Prot Protected Phases 2 6 4 Permitted Phases 6 4 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Actuated Green, g (s) 55.4 55.4 55.4 16.1 Actuated Green, g (s) 55.0 55.0 40.1 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Leerance Time (s) 5.0 5.0 4.0 Vehicle Ex		1.00		0.20	1.00	0.98			
Peak-hour factor, PHF 1.00 1.00 1.00 1.00 1.00 1.00 Adj. Flow (vph) 810 25 41 784 19 26 RTOR Reduction (vph) 1 0 0 0 21 0 Lane Group Flow (vph) 834 0 41 784 24 0 Turn Type NA Perm NA Prot Protected Phases 2 6 4 Permitted Phases 6 4 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 50.0 50.0 0.63 0.63 0.18 Clearance Time (s) 50.0 50.0 50.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 <t< td=""><td>Satd. Flow (perm)</td><td>1855</td><td></td><td>381</td><td>1863</td><td>1682</td><td></td><td></td><td></td></t<>	Satd. Flow (perm)	1855		381	1863	1682			
Adj. Flow (vph) 810 25 41 784 19 26 RTOR Reduction (vph) 1 0 0 0 21 0 Lane Group Flow (vph) 834 0 41 784 24 0 Turn Type NA Perm NA Prot Protected Phases 2 6 4 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 v/c Ratio 0.71 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00			1.00	1.00	1.00	1.00	1.00		
RTOR Reduction (vph) 1 0 0 0 21 0 Lane Group Flow (vph) 834 0 41 784 24 0 Turn Type NA Perm NA Prot Protected Phases 6 4 Permitted Phases 6 4 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 Incre									
Lane Group Flow (vph) 834 0 41 784 24 0 Turn Type NA Perm NA Prot Protected Phases 6 4 Permitted Phases 6 A Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>									
Protected Phases 2 6 4 Permitted Phases 6 4 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach LOS B B C Intersection Summary		834	0	41	784	24	0		
Protected Phases 2 6 4 Permitted Phases 6 4 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 V/s Ratio Prot c0.45 0.42 c0.01 V/s Ratio Perm 0.11 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach LOS B B C Intersection Summary		NA		Perm	NA	Prot			
Permitted Phases 6 Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach LOS B B C Intersection Summary									
Actuated Green, G (s) 55.4 55.4 55.4 16.1 Effective Green, g (s) 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 v/c Ratio 0.71 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B C C Intersection Summary				6					
Effective Green, g (s) 55.4 55.4 16.1 Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 v/c Ratio 0.71 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B C Intersection Summary		55.4			55.4	16.1			
Actuated g/C Ratio 0.63 0.63 0.63 0.18 Clearance Time (s) 5.0 5.0 4.0 Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 v/c Ratio 0.71 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B C Intersection Summary		55.4		55.4	55.4	16.1			
Vehicle Extension (s) 3.0 3.0 3.0 3.0 Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary		0.63		0.63	0.63	0.18			
Lane Grp Cap (vph) 1167 239 1172 307 v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 0.67 0.08 V/c Ratio 0.71 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C		5.0		5.0	5.0	4.0			
v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary	Vehicle Extension (s)	3.0		3.0	3.0	3.0			
v/s Ratio Prot c0.45 0.42 c0.01 v/s Ratio Perm 0.11 co.07 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary	Lane Grp Cap (vph)	1167		239	1172	307			
v/c Ratio 0.71 0.17 0.67 0.08 Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary		c0.45			0.42	c0.01			
Uniform Delay, d1 11.0 6.8 10.4 29.8 Progression Factor 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary	v/s Ratio Perm			0.11					
Progression Factor 1.00 1.00 1.00 1.00 Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary	v/c Ratio	0.71		0.17	0.67	0.08			
Incremental Delay, d2 3.8 0.3 1.5 0.5 Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary	Uniform Delay, d1	11.0		6.8	10.4	29.8			
Delay (s) 14.7 7.1 11.9 30.3 Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary	Progression Factor	1.00		1.00	1.00	1.00			
Level of Service B A B C Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary	Incremental Delay, d2	3.8		0.3	1.5	0.5			
Approach Delay (s) 14.7 11.7 30.3 Approach LOS B B C Intersection Summary	Delay (s)	14.7		7.1	11.9	30.3			
Approach LOS B B C Intersection Summary	Level of Service			А	В				
Intersection Summary	Approach Delay (s)	14.7			11.7	30.3			
	Approach LOS	В			В	С			
	Intersection Summary								
$oldsymbol{j}$	HCM 2000 Control Delay			13.7	Н	CM 2000	Level of Service	В	
HCM 2000 Volume to Capacity ratio 0.55		acity ratio							
Actuated Cycle Length (s) 88.0 Sum of lost time (s) 14.0								14.0	
Intersection Capacity Utilization 55.0% ICU Level of Service A Analysis Period (min) 15		ation			IC	CU Level c	f Service	A	

	•	•	†	~	>	ţ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		f)			ર્ન
Traffic Volume (veh/h)	0	8	10	0	9	5
Future Volume (Veh/h)	0	8	10	0	9	5
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	0	8	10	0	9	5
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume	33	10			10	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	33	10			10	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)	0.1	0.2				
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	99			99	
cM capacity (veh/h)	975	1071			1610	
					1010	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	8	10	14			
Volume Left	0	0	9			
Volume Right	8	0	0			
cSH	1071	1700	1610			
Volume to Capacity	0.01	0.01	0.01			
Queue Length 95th (ft)	1	0	0			
Control Delay (s)	8.4	0.0	4.7			
Lane LOS	А		Α			
Approach Delay (s)	8.4	0.0	4.7			
Approach LOS	А					
Intersection Summary						
Average Delay			4.1			
Intersection Capacity Utiliz	ation		17.4%	IC	U Level c	f Service
Analysis Period (min)			15	10	CECVOIC	n Joi vide
Analysis r chou (IIIIII)			10			

	-	•	•	•	•	<i>></i>	
Movement	EBT	EBR	WBL	WBT	NBL	NBR	
Lane Configurations	₽		ች	A	*/*		
Traffic Volume (vph)	590	12	7	689	27	44	
Future Volume (vph)	590	12	7	689	27	44	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost time (s)	5.0		5.0	5.0	4.0		
Lane Util. Factor	1.00		1.00	1.00	1.00		
Frt	1.00		1.00	1.00	0.92		
Flt Protected	1.00		0.95	1.00	0.98		
Satd. Flow (prot)	1858		1770	1863	1675		
Flt Permitted	1.00		0.35	1.00	0.98		
Satd. Flow (perm)	1858		647	1863	1675		
Peak-hour factor, PHF	1.00	1.00	1.00	1.00	1.00	1.00	
Adj. Flow (vph)	590	12	7	689	27	44	
RTOR Reduction (vph)	1	0	0	0	36	0	
Lane Group Flow (vph)	601	0	7	689	35	0	
Turn Type	NA		Perm	NA	Prot		
Protected Phases	2			6	4		
Permitted Phases			6				
Actuated Green, G (s)	55.4		55.4	55.4	16.1		
Effective Green, g (s)	55.4		55.4	55.4	16.1		
Actuated g/C Ratio	0.63		0.63	0.63	0.18		
Clearance Time (s)	5.0		5.0	5.0	4.0		
Vehicle Extension (s)	3.0		3.0	3.0	3.0		
Lane Grp Cap (vph)	1169		407	1172	306		
v/s Ratio Prot	0.32			c0.37	c0.02		
v/s Ratio Perm			0.01				
v/c Ratio	0.51		0.02	0.59	0.11		
Uniform Delay, d1	8.9		6.1	9.6	30.0		
Progression Factor	1.00		1.00	1.00	1.00		
Incremental Delay, d2	1.6		0.0	8.0	8.0		
Delay (s)	10.5		6.1	10.3	30.8		
Level of Service	В		Α	В	С		
Approach Delay (s)	10.5			10.3	30.8		
Approach LOS	В			В	С		
Intersection Summary							
HCM 2000 Control Delay			11.5	H	CM 2000	Level of Service	
HCM 2000 Volume to Capacit	ty ratio		0.46				
Actuated Cycle Length (s)			88.0		um of lost		
Intersection Capacity Utilization	on		48.0%	IC	U Level o	f Service	
Analysis Period (min)			15				

	-	•	•	•	•	~
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	1			4	W	
Traffic Volume (veh/h)	945	5	0	816	3	7
Future Volume (Veh/h)	945	5	0	816	3	7
Sign Control	Free			Free	Stop	•
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	945	5	0	816	3	7
Pedestrians	373	<u> </u>	U	010	J	,
Lane Width (ft)						
. ,						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)	NI			Ma		
Median type	None			None		
Median storage veh)	4000			00=		
Upstream signal (ft)	1288			325	0.00	
pX, platoon unblocked					0.69	
vC, conflicting volume			950		1764	948
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol			950		1882	948
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)						
tF (s)			2.2		3.5	3.3
p0 queue free %			100		94	98
cM capacity (veh/h)			723		54	316
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	950	816	10			
Volume Left	0	0	3			
Volume Right	5	0	7			
cSH	1700	723	128			
Volume to Capacity	0.56	0.00	0.08			
Queue Length 95th (ft)	0.00	0.00	6			
Control Delay (s)	0.0	0.0	35.4			
Lane LOS	0.0	0.0	55.4 E			
Approach Delay (s)	0.0	0.0	35.4			
Approach LOS	0.0	0.0	55.4 E			
•						
Intersection Summary						
Average Delay			0.2			
Intersection Capacity Utiliz	ation		60.0%	IC	U Level c	of Service
Analysis Period (min)			15			

	-	•	•	•	1	<i>></i>		
Movement	EBT	EBR	WBL	WBT	NBL	NBR		
Lane Configurations	1 >		ሻ	†	W			
Traffic Volume (vph)	829	26	42	803	20	27		
Future Volume (vph)	829	26	42	803	20	27		
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900		
Total Lost time (s)	5.0		5.0	5.0	4.0			
Lane Util. Factor	1.00		1.00	1.00	1.00			
Frt	1.00		1.00	1.00	0.92			
Flt Protected	1.00		0.95	1.00	0.98			
Satd. Flow (prot)	1855		1770	1863	1682			
Flt Permitted	1.00		0.19	1.00	0.98			
Satd. Flow (perm)	1855		359	1863	1682			
Peak-hour factor, PHF	1.00	1.00	1.00	1.00	1.00	1.00		
Adj. Flow (vph)	829	26	42	803	20	27		
RTOR Reduction (vph)	1	0	0	0	22	0		
Lane Group Flow (vph)	854	0	42	803	25	0		
Turn Type	NA		Perm	NA	Prot			
Protected Phases	2			6	4			
Permitted Phases			6					
Actuated Green, G (s)	55.4		55.4	55.4	16.1			
Effective Green, g (s)	55.4		55.4	55.4	16.1			
Actuated g/C Ratio	0.63		0.63	0.63	0.18			
Clearance Time (s)	5.0		5.0	5.0	4.0			
Vehicle Extension (s)	3.0		3.0	3.0	3.0			
Lane Grp Cap (vph)	1167		226	1172	307			
v/s Ratio Prot	c0.46			0.43	c0.01			
v/s Ratio Perm			0.12					
v/c Ratio	0.73		0.19	0.69	0.08			
Uniform Delay, d1	11.2		6.8	10.6	29.8			
Progression Factor	1.00		1.00	1.00	1.00			
Incremental Delay, d2	4.1		0.4	1.7	0.5			
Delay (s)	15.3		7.2	12.3	30.3			
Level of Service	В		Α	В	С			
Approach Delay (s)	15.3			12.0	30.3			
Approach LOS	В			В	С			
Intersection Summary								
HCM 2000 Control Delay			14.1	Н	CM 2000	Level of Service	В	
HCM 2000 Volume to Capa	city ratio		0.57					
Actuated Cycle Length (s)			88.0	S	um of lost	time (s)	14.0	
Intersection Capacity Utiliza	ation		56.0%	IC	CU Level c	of Service	В	
Analysis Period (min)			15					

	-	•	•	•	•	/
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	<u> </u>			4	W	
Traffic Volume (veh/h)	593	7	2	715	11	0
Future Volume (Veh/h)	593	7	2	715	11	0
Sign Control	Free	•	_	Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	593	7	2	715	11	0
Pedestrians	000	•	_		• • •	
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)	140110			140110		
Upstream signal (ft)	1288			325		
pX, platoon unblocked	1200			020	0.76	
vC, conflicting volume			600		1316	596
vC1, stage 1 conf vol			000		1010	330
vC2, stage 2 conf vol						
vCu, unblocked vol			600		1258	596
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)			7.1		0.7	٠.۷
tF (s)			2.2		3.5	3.3
p0 queue free %			100		92	100
cM capacity (veh/h)			977		144	503
					177	300
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	600	717	11			
Volume Left	0	2	11			
Volume Right	7	0	0			
cSH	1700	977	144			
Volume to Capacity	0.35	0.00	0.08			
Queue Length 95th (ft)	0	0	6			
Control Delay (s)	0.0	0.1	32.2			
Lane LOS		Α	D			
Approach Delay (s)	0.0	0.1	32.2			
Approach LOS			D			
Intersection Summary						
Average Delay			0.3			
Intersection Capacity Utilizat	ion		49.2%	IC	U Level o	f Service
Analysis Period (min)			15			

	-	•	•	•	•	<i>></i>	
Movement	EBT	EBR	WBL	WBT	NBL	NBR	
Lane Configurations	₽		*	A	*/*		
Traffic Volume (vph)	590	12	7	691	27	44	
Future Volume (vph)	590	12	7	691	27	44	
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	
Total Lost time (s)	5.0		5.0	5.0	4.0		
Lane Util. Factor	1.00		1.00	1.00	1.00		
Frt	1.00		1.00	1.00	0.92		
Flt Protected	1.00		0.95	1.00	0.98		
Satd. Flow (prot)	1858		1770	1863	1675		
FIt Permitted	1.00		0.35	1.00	0.98		
Satd. Flow (perm)	1858		647	1863	1675		
Peak-hour factor, PHF	1.00	1.00	1.00	1.00	1.00	1.00	
Adj. Flow (vph)	590	12	7	691	27	44	
RTOR Reduction (vph)	1	0	0	0	36	0	
Lane Group Flow (vph)	601	0	7	691	35	0	
Turn Type	NA		Perm	NA	Prot		
Protected Phases	2			6	4		
Permitted Phases			6				
Actuated Green, G (s)	55.4		55.4	55.4	16.1		
Effective Green, g (s)	55.4		55.4	55.4	16.1		
Actuated g/C Ratio	0.63		0.63	0.63	0.18		
Clearance Time (s)	5.0		5.0	5.0	4.0		
Vehicle Extension (s)	3.0		3.0	3.0	3.0		
Lane Grp Cap (vph)	1169		407	1172	306		
v/s Ratio Prot	0.32			c0.37	c0.02		
v/s Ratio Perm			0.01				
v/c Ratio	0.51		0.02	0.59	0.11		
Uniform Delay, d1	8.9		6.1	9.6	30.0		
Progression Factor	1.00		1.00	1.00	1.00		
Incremental Delay, d2	1.6		0.0	0.8	0.8		
Delay (s)	10.5		6.1	10.4	30.8		
Level of Service	В		Α	В	С		
Approach Delay (s)	10.5			10.3	30.8		
Approach LOS	В			В	С		
Intersection Summary							
HCM 2000 Control Delay			11.5	H	CM 2000	Level of Service	
HCM 2000 Volume to Capacit	ty ratio		0.47				
Actuated Cycle Length (s)			88.0		um of lost		
Intersection Capacity Utilization	on		48.1%	IC	U Level o	f Service	
Analysis Period (min)			15				

	•	•	†	/	\	+	
Movement	WBL	WBR	NBT	NBR	SBL	SBT	
Lane Configurations	¥		1>			सी	
Traffic Volume (veh/h)	0	7	4	0	4	5	
Future Volume (Veh/h)	0	7	4	0	4	5	
Sign Control	Stop		Free			Free	
Grade	0%		0%			0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Hourly flow rate (vph)	0	7	4	0	4	5	
Pedestrians							
Lane Width (ft)							
Walking Speed (ft/s)							
Percent Blockage							
Right turn flare (veh)							
Median type			None			None	
Median storage veh)							
Upstream signal (ft)							
pX, platoon unblocked							
vC, conflicting volume	17	4			4		
vC1, stage 1 conf vol	.,				•		
vC2, stage 2 conf vol							
vCu, unblocked vol	17	4			4		
tC, single (s)	6.4	6.2			4.1		
tC, 2 stage (s)	V. 1	V.2					
tF (s)	3.5	3.3			2.2		
p0 queue free %	100	99			100		
cM capacity (veh/h)	999	1080			1618		
			OD 4				
Direction, Lane # Volume Total	WB 1	NB 1	SB 1				
	7	4	9				
Volume Left	0	0	4				
Volume Right	7	0	0				
cSH	1080	1700	1618				
Volume to Capacity	0.01	0.00	0.00				
Queue Length 95th (ft)	0	0	0				
Control Delay (s)	8.4	0.0	3.2				
Lane LOS	A	0.0	Α				
Approach Delay (s)	8.4	0.0	3.2				
Approach LOS	Α						
Intersection Summary							
Average Delay			4.4				
Intersection Capacity Utilizat	tion		13.8%	IC	U Level o	of Service	
Analysis Period (min)			15				

	-	\rightarrow	•	←	^	~
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	1			4	N/	
Traffic Volume (veh/h)	935	10	4	816	6	12
Future Volume (Veh/h)	935	10	4	816	6	12
Sign Control	Free			Free	Stop	'-
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	935	10	4	816	6	12
Pedestrians	700	10		010	0	12
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)	INOTIC			NOTIC		
Upstream signal (ft)	1288			325		
pX, platoon unblocked	1200			323	0.69	
vC, conflicting volume			945		1764	940
vC1, stage 1 conf vol			743		1704	740
vC2, stage 2 conf vol						
vCu, unblocked vol			945		1884	940
tC, single (s)			4.1		6.4	6.2
tC, 3ingle (s)			7.1		0.4	0.2
tF (s)			2.2		3.5	3.3
p0 queue free %			99		89	96
cM capacity (veh/h)			726		53	320
					33	320
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	945	820	18			
Volume Left	0	4	6			
Volume Right	10	0	12			
cSH	1700	726	120			
Volume to Capacity	0.56	0.01	0.15			
Queue Length 95th (ft)	0	0	13			
Control Delay (s)	0.0	0.2	40.4			
Lane LOS		Α	Е			
Approach Delay (s)	0.0	0.2	40.4			
Approach LOS			Е			
Intersection Summary						
Average Delay			0.5			
Intersection Capacity Utiliz	zation		59.8%	IC	CU Level o	of Service
Analysis Period (min)	Lation		15	10	O LEVEL	J JEI VICE
Analysis Pellou (IIIIII)			15			

Movement EBT EBR WBL WBT NBL NBR Lane Configurations 1
Lane Configurations Image: Configuration of the confi
Traffic Volume (vph) 834 26 42 807 20 27 Future Volume (vph) 834 26 42 807 20 27 Ideal Flow (vphpl) 1900 1900 1900 1900 1900 1900 Total Lost time (s) 5.0 5.0 5.0 4.0 Lane Util. Factor 1.00 1.00 1.00 1.00 Frt 1.00 1.00 0.92
Future Volume (vph) 834 26 42 807 20 27 Ideal Flow (vphpl) 1900 1900 1900 1900 1900 Total Lost time (s) 5.0 5.0 4.0 Lane Util. Factor 1.00 1.00 1.00 Frt 1.00 1.00 0.92
Ideal Flow (vphpl) 1900 1900 1900 1900 1900 Total Lost time (s) 5.0 5.0 5.0 4.0 Lane Util. Factor 1.00 1.00 1.00 1.00 Frt 1.00 1.00 0.92
Total Lost time (s) 5.0 5.0 4.0 Lane Util. Factor 1.00 1.00 1.00 Frt 1.00 1.00 0.92
Lane Util. Factor 1.00 1.00 1.00 Frt 1.00 1.00 0.92
Frt 1.00 1.00 0.92
Elt Protoctod 1.00 0.05 1.00 0.09
FILE FIDECTED 1.00 0.70 1.00 0.70
Satd. Flow (prot) 1855 1770 1863 1682
Flt Permitted 1.00 0.19 1.00 0.98
Satd. Flow (perm) 1855 353 1863 1682
Peak-hour factor, PHF 1.00 1.00 1.00 1.00 1.00
Adj. Flow (vph) 834 26 42 807 20 27
RTOR Reduction (vph) 1 0 0 0 22 0
Lane Group Flow (vph) 859 0 42 807 25 0
Turn Type NA Perm NA Prot
Protected Phases 2 6 4
Permitted Phases 6
Actuated Green, G (s) 55.4 55.4 16.1
Effective Green, g (s) 55.4 55.4 16.1
Actuated g/C Ratio 0.63 0.63 0.63 0.18
Clearance Time (s) 5.0 5.0 4.0
Vehicle Extension (s) 3.0 3.0 3.0
Lane Grp Cap (vph) 1167 222 1172 307
v/s Ratio Prot c0.46 0.43 c0.01
v/s Ratio Perm 0.12
v/c Ratio 0.74 0.19 0.69 0.08
Uniform Delay, d1 11.3 6.9 10.7 29.8
Progression Factor 1.00 1.00 1.00
Incremental Delay, d2 4.2 0.4 1.7 0.5
Delay (s) 15.4 7.3 12.4 30.3
Level of Service B A B C
Approach Delay (s) 15.4 12.1 30.3
Approach LOS B C
Intersection Summary
HCM 2000 Control Delay 14.2 HCM 2000 Level of Service B
HCM 2000 Volume to Capacity ratio 0.57
Actuated Cycle Length (s) 88.0 Sum of lost time (s) 14.0
Intersection Capacity Utilization 56.3% ICU Level of Service B
Analysis Period (min) 15

	•	•	†	~	>	ţ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		f)			ર્ન
Traffic Volume (veh/h)	0	8	10	0	9	5
Future Volume (Veh/h)	0	8	10	0	9	5
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	0	8	10	0	9	5
Pedestrians						
Lane Width (ft)						
Walking Speed (ft/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (ft)						
pX, platoon unblocked						
vC, conflicting volume	33	10			10	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	33	10			10	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)	0.1	0.2				
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	99			99	
cM capacity (veh/h)	975	1071			1610	
					1010	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	8	10	14			
Volume Left	0	0	9			
Volume Right	8	0	0			
cSH	1071	1700	1610			
Volume to Capacity	0.01	0.01	0.01			
Queue Length 95th (ft)	1	0	0			
Control Delay (s)	8.4	0.0	4.7			
Lane LOS	А		Α			
Approach Delay (s)	8.4	0.0	4.7			
Approach LOS	А					
Intersection Summary						
Average Delay			4.1			
Intersection Capacity Utiliz	ation		17.4%	IC	U Level c	f Service
Analysis Period (min)			15	10	CECVOIC	n Joi vide
Analysis r chou (IIIIII)			10			